

COVERING NOTE:
 FOR COMPETITION CRAFT
 USE LIGHTEST WEIGHT
 SILKSPAN WITH TWO COATS
 CLEAR-TWO COATS COLOR
 DOPE MAX.

1/16" sq. STRINGER
 POSITIONS

MARK WITH
 SOFT PENCIL

1/4" X 1/4"
 Balsa SPAR

CRUTCH

WING TIP
 FORMERS AND
 TRAILING EDGE OF
 1/8" Balsa SHEET

W-1

W-2

W-3

F-4-T

F-2-T

F-2-B

F-4-B

F-5-T

F-5-B

F-3-T

F-1-T

F-3-B

F-1-B

F-9-T

F-9-B

CUT FORMERS FROM
 1/16" SHEET Balsa

3/8" DIHEDRAL O.A.

WING TIP

WHITE TAPE FAIRING

STAB.

ALUM. ROD

GEAR BLOCK

1/2" Balsa PLANK

1/4" PLANK

ALUM. AXLE AND SLEEVE

FRONT VIEW

NOTE: BEND

FIN

1/6" WHITE CHARTPAK
 ON WIND
 SCREEN

NOTE: DIRECTION
 OF GRAIN

F-7-T

F-7-B

F-6-T

F-6-B

F-8-T

F-8-B

F-7-T

F-7-B

